

UNIVERSAL SERIES™

TECHNICAL DATA

The Universal Series™ offers a patented, high-performance fiberglass solution for window walls, windows and doors, and storefront glazing.

Designed and manufactured in North America, the Universal Series™ features an innovative, commercial-grade fiberglass frame boasting 150% improved thermal performance compared to traditional aluminum windows.

Custom configured and built-to-suit project requirements—and available in virtually any color—the Universal Series™ allows developers and architects to dramatically improve the overall thermal performance of buildings, without sacrificing glazing area.

- Custom sizes & configurations
- AW Performance Class designation (casements, awnings, fixed windows)
- Low-VOC standard & custom colors meet AAMA 625 performance criteria
- Double (one Low-E) & Triple (two Low-E)
- LBC Red List Free and Energy-Star rated

UNIVERSAL SERIES™

Technical Data Sheet



DOUBLE GLAZED - NFRC THERMAL PERFORMANCE SUMMARY VISION AREAS



WINDOWS & DOORS - DOUBLE GLAZED										
LOW-E OPTIONS	CENTER-OF-GLASS DATA			U _w (U-VALUE OF WINDOW) PER NFRC METHOD [BTU/HR*FT ² *F]						
CARDINAL (90% ARGON FILL, UNO)	U _g	SHGC	VT	FIXED	CASEMENT	AWNING	TILT & TURN	HOPPER	SWING DOOR	SLIDING DOOR
STANDARD DOUBLE GLAZED (ONE LOW-E ON SURFACE #2 OR #3 / STAINLESS STEEL SPACER)										
180 (#3)	0.26	0.68	0.79	0.26	0.25	0.25	0.25	0.24	0.24	0.24
270 (#2)	0.25	0.37	0.70	0.25	0.24	0.24	0.24	0.24	0.23	0.23
366 (#2)	0.24	0.27	0.65	0.24	0.24	0.24	0.23	0.23	0.23	0.23
340 (#2)	0.25	0.18	0.39	0.25	0.24	0.25	0.24	0.23	0.23	0.23
PREMIUM DOUBLE GLAZED (TWO LOW-E ON SURFACES #2 & #4 / STAINLESS STEEL SPACER)										
180/i89	0.21	0.62	0.77	0.21	0.22	-	-	-	0.20	0.21
270/i89	0.20	0.36	0.69	0.21	0.21	-	-	-	0.20	0.20
366/i89	0.20	0.27	0.63	0.20	0.21	-	-	-	0.19	0.20
340/i89	0.20	0.17	0.38	0.20	0.21	-	-	-	0.19	0.20

NOTE: Triple Glazed information can be found on page 3

TRIPLE GLAZED - NFRC THERMAL PERFORMANCE SUMMARY VISION AREAS



WINDOWS & DOORS - TRIPLE GLAZED										
LOW-E OPTIONS	CENTER-OF-GLASS DATA			U _w (U-VALUE OF WINDOW) PER NFRC METHOD [BTU/HR*FT ² *F]						
CARDINAL (90% ARGON FILL, UNO)	U _g	SHGC	VT	FIXED	CASEMENT	AWNING	TILT & TURN	HOPPER	SWING DOOR	SLIDING DOOR
STANDARD TRIPLE GLAZED (TWO LOW-E ON SURFACES #2 & #5 / STAINLESS STEEL SPACER)										
180/180	0.13	0.56	0.70	0.15	0.17	0.17	0.15	0.16	0.15	0.15
270/180	0.13	0.33	0.62	0.14	0.17	0.17	0.15	0.16	0.15	0.15
366/180	0.13	0.25	0.57	0.14	0.17	0.17	0.15	0.16	0.15	0.15
340/180	0.13	0.16	0.34	0.14	0.17	0.17	0.15	0.16	0.15	0.15
OPTIONS W/ CAPILLARY TUBES – AIR FILL (TWO LOW-E ON SURFACES #2 & #5 / STAINLESS STEEL SPACER)										
366/180	0.16	0.25	0.57	0.17	0.18	0.18	0.17	0.18	0.17	0.17
STANDARD TRIPLE GLAZED (TWO LOW-E ON SURFACES #2 & #5 / TRISEAL SUPER SPACER)										
180/180	0.13	0.56	0.70	0.15	0.16	0.17	0.15	0.16	0.15	0.15
270/180	0.13	0.33	0.62	0.14	0.16	0.16	0.15	0.16	0.14	0.14
366/180	0.13	0.25	0.57	0.14	0.16	0.16	0.15	0.16	0.13	0.13
340/180	0.13	0.16	0.34	0.14	0.16	0.16	0.15	0.16	0.14	0.14
PREMIUM TRIPLE GLAZED (THREE LOW-E ON SURFACES #2, #4 & #6 / STAINLESS STEEL SPACER)										
180/180/i89	0.12	0.53	0.68	0.13	0.16	0.16	0.14	0.16	0.14	0.14
270/180/i89	0.11	0.32	0.60	0.13	0.16	0.16	0.14	0.15	0.14	0.14
366/180/i89	0.11	0.24	0.56	0.13	0.16	0.16	0.14	0.15	0.13	0.13
340/180/i89	0.11	0.15	0.33	0.13	0.16	0.16	0.14	0.15	0.14	0.14
PREMIUM TRIPLE GLAZED (THREE LOW-E ON SURFACES #2, #4 & #6 / TRISEAL SUPER SPACER)										
180/180/i89	0.12	0.53	0.68	0.13	0.16	0.16	0.14	0.15	0.14	0.14
270/180/i89	0.11	0.32	0.60	0.13	0.15	0.15	0.14	0.15	0.13	0.13
366/180/i89	0.11	0.24	0.56	0.13	0.15	0.15	0.13	0.15	0.13	0.13
340/180/i89	0.11	0.15	0.33	0.13	0.15	0.15	0.13	0.15	0.13	0.13

NOTE: Double Glazed information can be found on page 2



INTERNATIONAL PASSIVE HOUSE INSTITUTE [PHI] - THERMAL DATA

LOW-E OPTIONS	CENTER-OF-GLASS DATA			U _w (U-VALUE OF WINDOW) PER EN ISO 10077 [W / m ² K]			
	U _g	SHGC	VT	INSWING WINDOW	FIXED WINDOW	INSWING DOOR	SLIDING DOOR
Calibration Panel	0.700			0.805	0.773	0.780	0.756
180/180	0.646	0.555	0.690	0.766	0.728	0.748	0.717
270/180	0.612	0.352	0.607	0.742	0.699	0.725	0.692
366/180	0.594	0.270	0.563	0.729	0.684	0.713	0.678
340/180	0.602	0.166	0.337	0.735	0.691	0.719	0.684
180/180/i89	0.604	0.531	0.675	0.736	0.693	0.720	0.686
270/180/i89	0.574	0.340	0.593	0.715	0.667	0.700	0.664
366/180/i89	0.558	0.262	0.550	0.704	0.654	0.689	0.652
340/180/i89	0.565	0.165	0.331	0.709	0.660	0.694	0.657

Modeled Size: Windows 1230W x 1480H | Swing Door 1100W x 2200H | Sliding Door 2400W x 2500H

Spacer: SuperSpacer® TriSeal™ by Edgetech



INTERNATIONAL PASSIVE HOUSE INSTITUTE [PHI] - FRAME DATA

		WIDTH [MM]	U-VALUES [W / m ² K]	Psi VALUES [W / mK]
INSWING WINDOW		105	0.88	0.021
FIXED WINDOW		58	0.81	0.020
INSWING DOOR	Sides & Head	132	0.79	0.022
	Sill	146	0.86	0.022
SLIDING DOOR	Bottom Sash	168	0.74	0.021
	Bottom Fixed	81	0.74	0.022
	Side Fixed	58	0.81	0.020
	Side Sash	158	0.73	0.020
	Top Sash	168	0.79	0.021
	Top Fixed	81	0.76	0.023
	Mullion	202	0.74	0.020

Modeled Size: Windows 1230W x 1480H | Swing Door 1100W x 2200H | Sliding Door 2400W x 2500H

Spacer: SuperSpacer® TriSeal™ by Edgetech



PASSIVE HOUSE INSTITUTE US [PHIUS] - WINDOWS

LOW-E OPTIONS	CENTER-OF-GLASS DATA			UW (U-VALUE OF WINDOW) PER EN ISO 10077 [W / m ² K]							
	U _g	SHGC	VT	FIXED EXT GLAZED		FIXED INT GLAZED		OUTSWING: CASEMENT, AWNING		INSWING: TILT & TURN, HOPPER	
				U _w	U _f	U _w	U _f	U _w	U _f	U _w	U _f
180/180	0.128	0.514	0.690	0.16	0.18	0.16	0.19	0.17	0.19	0.16	0.18
366/180	0.120	0.239	0.563	0.15	0.17	0.15	0.19	0.16	0.19	0.16	0.18
180/180/i89	0.111	0.487	0.675	0.14	0.20	0.15	0.22	0.16	0.20	0.15	0.20
366/180/i89	0.105	0.230	0.550	0.14	0.20	0.14	0.22	0.15	0.20	0.15	0.20

Spacer: Stainless Steel Endur Spacer by Cardinal

Zones: Values for climate zone4, zone Marine North, and/or zone Marine South. Request full PHIUS certificates for PSI values, additional performance data, and climate zone recommendations.

ACOUSTIC PERFORMANCE

WINDOWS				
	GLAZING	SAMPLE SIZE	STC	OITC
FIXED WINDOW (ASTM E90)	Double 6/4	47.25" x 59.00"	34	28
FIXED WINDOW (ASTM E90)	Triple 6Lami/4/6	47.25" x 59.00"	37	27
TILT & TURN (ASTM E90)	Double 6/4	47.25" x 59.00"	35	28
TILT & TURN (ASTM E90)	Triple 6Lami/4/6	47.25" x 59.00"	37	28
GLASS-ONLY (CALCULATED VALUES) 1" IGU NOMINAL	Double 6/6	Center-of-glass	35	28
GLASS-ONLY (CALCULATED VALUES) 1" IGU NOMINAL	Double 6Lami/6	Center-of-glass	38	31
GLASS-ONLY (CALCULATED VALUES) 1" IGU NOMINAL	Double 6Lami/6Lami	Center-of-glass	40	34
GLASS-ONLY (CALCULATED VALUES) 1.25" IGU NOMINAL	Double 6/6	Center-of-glass	38	31
GLASS-ONLY (CALCULATED VALUES) 1.25" IGU NOMINAL	Double 6Lami/6	Center-of-glass	39	32
GLASS-ONLY (CALCULATED VALUES) 1.25" IGU NOMINAL	Double 6Lami/6Lami	Center-of-glass	41	35
GLASS-ONLY (CALCULATED VALUES) 1.70" IGU NOMINAL	Triple 6/4/6	Center-of-glass	39	31
GLASS-ONLY (CALCULATED VALUES) 1.70" IGU NOMINAL	Triple 6Lami/4/6	Center-of-glass	41	34
GLASS-ONLY (CALCULATED VALUES) 1.70" IGU NOMINAL	Triple 4/4/4	Center-of-glass	36	28

NOTE: Glass-only calculated values for STC and OITC represent approximate values.



NAFS KEY PERFORMANCE DATA - WINDOWS & DOORS

TYPE		TESTED SIZE [INCHES]	DESIGN WIND PRESSURE PSF (PA)	WATER INFILTRATION PSF (PA)	NAFS DESIGNATORS	AIR INFILTRATION [L/s*M ²]	AIR EXFILTRATION [L/s*M ²]
OUTSWING	CASEMENT	36" x 60"	60 (2880)	15 (730)	AW-PG60-C	0.01	0.06
	CASEMENT	36" x 84"	60 (2880)	15 (730)	CW-PG60-C	0.06	0.02
	AWNING	60" X 36"	60 (2880)	15 (730)	AW-PG60-AP	0.05	0.29
	AWNING	84" x 36"	60 (2880)	15 (730)	CW-PG60-AP	0.00	0.00
	AWNING	48" x 84"	55 (2640)	15 (730)	CW-PG55-AP	0.01	0.01
	AWNING	76" x 60"	35 (1680)	15 (730)	CW-PG35-AP	0.00	0.00
INSWING	TILT & TURN	48" x 72"	80 (3840)	15 (730)	CW-PG80-DAW	0.00	0.01
	TILT & TURN	60" x 99"	45 (2160)	15 (730)	LC-PG45-AP	0.00	0.00
	HOPPER	84" x 36"	85 (4080)	15 (730)	CW-PG85-AP	0.07	0.06
	HOPPER	76" x 60"	60 (2880)	15 (730)	CW-PG60-AP	0.11	0.13
FIXED	FIXED	76" x 120"	60 (2880)	15 (730)	AW-PG60-FW	0.01	0.01
	FIXED	144" x 60"	100 (4800)	15 (730)	CW-PG100-FW	0.00	0.00
	FIXED	102" x 84"	95 (4320)	15 (730)	CW-PG95-FW	0.00	0.00
DOORS	OUTSWING (SINGLE)	60" x 120"	40 (1920)	15 (730)	CW-PG40-SHD	0.21	0.18
	OUTSWING (DOUBLE)	96" x 108"	20 (960)	15 (730)	R-PG20-SHD	0.21	0.18
	INSWING (SINGLE)	60" x 120"	45 (2160)	15 (730)	R-PG45-DASHD	0.09	0.03
	INSWING (DOUBLE)	96" x 108"	35 (1680)	15 (730)	R-PG35-SHD	0.02	0.02
	SLIDING (SINGLE)	96" x 96"	45 (2160)	15 (730)	CW-PG45-SD	0.05	0.07
	SLIDING (DOUBLE)	240" x 108"	20 (960)	15 (730)	R-PG20-SD	0.01	0.02
	SLIDING (DOUBLE)	198" x 96"	30 (1440)	15 (730)	CW-PG30-SD	0.00	0.00

NOTE: Dimensions above indicate NAFS performance tested sizes which may exceed common size limits available. For minimum/maximum sizes available, please consult Cascadia's Vent Size Charts.

Air Infiltration and Exfiltration tests the overall assembly at 75 Pa. All windows meet and surpass the US and Canadian air leakage performance requirements for A3/Fixed

AVAILABLE WINDOW SIZES

	OUTSIDE-OF-FRAME				PERFORMANCE GRADE	MAX. WEIGHT (LBS)
	MIN. WIDTH (IN)	MIN. HEIGHT (IN)	MAX. WIDTH (IN)	MAX. HEIGHT (IN)		
Fixed Glazing	6	9	84	102	PG 95	400
Fixed Glazing	6	9	60	144	PG 100	400
Fixed Glazing	6	9	76	120	PG 60	400

Dimensions can be rotated 90 degrees

OPERABLE WINDOWS						
Casement (outswing)	18.75	22.625	36	72	PG 60	220
Awning (outswing)	20	22.625	55	47	PG 55	176
Tilt & Turn (inswing)	24	30	60	99	PG 80 up to 48"x72" / PG 45 at larger sizes	286
Hopper (inswing)	24	24	55	47	PG 60	176
SWING DOORS						
Single door (outswing)	24	60	60	120	PG 40	220
Single door (inswing)	24	60	58	105	PG 45	220
Double door (outswing)	24	60	96	108	PG 20	220
Double door (inswing)	24	60	94	105	PG 35	220
SLIDING DOORS						
Sliding single door (XO)	27	60	96	96	PG 45	220/sash
Sliding single door (XO)	27	60	118	105	PG 20	220/sash
Sliding single door (XO)	27	60	144	96	PG 30	220/sash
Sliding single door (XO)	27	60	177	105	PG 20	220/sash
Sliding double door (OXXO)	27	60	192	96	PG 30	220/sash
Sliding double door (OXXO)	27	60	236	105	PG 20	220/sash

Double door sizes shown include operable and fixed portions

GLASS WEIGHTS

GLASS THICKNESS	GLASS WEIGHTS (LBS/SQ FT)		
	MONOLITHIC	DOUBLE GLAZED	TRIPLE GLAZED
3.9 mm	2.18	4.36	6.54
4.7 mm	2.605	5.21	7.815
5.7 mm	3.155	6.31	9.465