

UNIVERSAL SERIES™

CURTAIN WALL VENT ADAPTER - TECHNICAL DATA

Cascadia's Fiberglass Curtain Wall Vent Adapter allows for the integration of high-performance fiberglass vent components into a traditional aluminum curtain wall assembly.

Compatible with most curtain wall systems, Cascadia's Fiberglass Curtain Wall Vent Adapter boasts 100%-250% improved thermal performance compared to traditional aluminum vents, improving the thermal performance of the entire curtain wall system.

- Compatible with most curtain wall systems (custom configurations available)
- Commercial-grade fiberglass frames
- Available with double & triple-glazed Low-E insulated glass units (IGUs)
- Living Building Challenge Red List Free
- Modelled lifespan of ≈80 years



NFRC THERMAL PERFORMANCE SUMMARY - VISION AREAS

WINDOWS & DOORS - DOUBLE GLAZED				
LOW-E OPTIONS	CENTER-OF-GLASS DATA			U _w (U-VALUE OF WINDOW) PER NFRC METHOD [BTU/HR*FT²*F]
CARDINAL (90% ARGON FILL, UNO)	U _g	SHGC	VT	AWNING
STANDARD DOUBLE GLAZED (ONE LOW-E ON SURFACE #2 OR #3 / STAINLESS STEEL SPACER)				
180 (#3)	0.26	0.68	0.79	0.25
270 (#2)	0.25	0.37	0.70	0.25
366 (#2)	0.24	0.27	0.65	0.24
340 (#2)	0.25	0.18	0.39	0.25
STANDARD TRIPLE GLAZED (TWO LOW-E ON SURFACES #2 & #5 / STAINLESS STEEL SPACER)				
180/180	0.13	0.56	0.70	0.17
270/180	0.13	0.33	0.62	0.17
366/180	0.13	0.25	0.57	0.17
340/180	0.13	0.16	0.34	0.17
OPTIONS W/ CAPILLARY TUBES – AIR FILL (TWO LOW-E ON SURFACES #2 & #5 / STAINLESS STEEL SPACER)				
366/180	0.16	0.25	0.57	0.18
STANDARD TRIPLE GLAZED (TWO LOW-E ON SURFACES #2 & #5 / TRISEAL SUPER SPACER)				
180/180	0.13	0.56	0.70	0.17
270/180	0.13	0.33	0.62	0.16
366/180	0.13	0.25	0.57	0.16
340/180	0.13	0.16	0.34	0.16
PREMIUM TRIPLE GLAZED (THREE LOW-E ON SURFACES #2, #4 & #6 / STAINLESS STEEL SPACER)				
180/180/i89	0.12	0.53	0.68	0.16
270/180/i89	0.11	0.32	0.60	0.16
366/180/i89	0.11	0.24	0.56	0.16
340/180/i89	0.11	0.15	0.33	0.16
PREMIUM TRIPLE GLAZED (THREE LOW-E ON SURFACES #2, #4 & #6 / TRISEAL SUPER SPACER)				
180/180/i89	0.12	0.53	0.68	0.16
270/180/i89	0.11	0.32	0.60	0.15
366/180/i89	0.11	0.24	0.56	0.15

Double-Glazed Glass: 6mm-13mm-6mm

Triple-Glazed Glass: 6mm-13mm-6mm-13mm-6mm

NOTE: Exact thermal performance of awning window in final curtain wall assembly subject to specific project configuration. Performance of specific project configuration should be independently verified.

UNIVERSAL SERIES™

Curtain Wall Vent Adapter - Technical Data Sheet

CASCADIA
WINDOWS & DOORS



NAFS KEY PERFORMANCE DATA - WINDOWS & DOORS

TYPE		TESTED SIZE [INCHES]	DESIGN WIND PRESSURE PSF (PA)	WATER INFILTRATION PSF (PA)	NAFS DESIGNATORS	AIR INFILTRATION [L/s*M²]	AIR EXFILTRATION [L/s*M²]
OUTSWING	AWNING	60" X 36"	60 (2880)	15 (730)	AW-PG60-AP	0.05	0.29
	AWNING	84" x 36"	60 (2880)	15 (730)	CW-PG60-AP	0.00	0.00
	AWNING	48" x 84"	55 (2640)	15 (730)	CW-PG55-AP	0.01	0.01
	AWNING	76" x 60"	35 (1680)	15 (730)	CW-PG35-AP	0.00	0.00

NOTE: Dimensions above indicate NAFS performance tested sizes which may exceed common size limits available. For minimum/maximum sizes available, please consult Cascadia's Vent Size Charts.

Air Infiltration and Exfiltration tests the overall assembly at 75 Pa. All windows meet and surpass the US and Canadian air leakage performance requirements for A3/Fixed

AVAILABLE WINDOW SIZES

	OUTSIDE-OF-FRAME				PERFORMANCE GRADE	MAX. WEIGHT (LBS)
	MIN. WIDTH (IN)	MIN. HEIGHT (IN)	MAX. WIDTH (IN)	MAX. HEIGHT (IN)		
OPERABLE WINDOWS						
Awning (outswing)	20	22.625	55	47	PG 55	176