

# UNIVERSAL SERIES™

## CURTAIN WALL VENT ADAPTER - TECHNICAL DATA

Cascadia's Fiberglass Curtain Wall Vent Adapter allows for the integration of high-performance fiberglass vent components into a traditional aluminum curtain wall assembly.

Compatible with most curtain wall systems, Cascadia's Fiberglass Curtain Wall Vent Adapter boasts 100%-250% improved thermal performance compared to traditional aluminum vents, improving the thermal performance of the entire curtain wall system.

- Compatible with most curtain wall systems (custom configurations available)
- Commercial-grade fiberglass frames
- Available with double & triple-glazed Low-E insulated glass units (IGUs)
- Living Building Challenge Red List Free
- Modelled lifespan of ≈80 years

# UNIVERSAL SERIES™

Curtain Wall Vent Adapter - Technical Data Sheet

**CASCADIA**  
WINDOWS & DOORS



## NFRC THERMAL PERFORMANCE SUMMARY - VISION AREAS

### WINDOWS - DOUBLE GLAZED

| LOW-E OPTIONS                             | CENTER-OF-GLASS DATA |      |      | $U_w$ (U-VALUE OF WINDOW) PER NFRC METHOD [BTU/HR*FT <sup>2</sup> *F] |        |             |
|---|----------------------|------|------|---|--------|-------------|
|   | $U_g$                | SHGC | VT   | CASEMENT  | AWNING | TIPT & TURN |
| <b>CARDINAL<br/>(90% ARGON FILL, UNO)</b> |                      |      |      |   |        |             |
| 180 (#3)                                  | 0.26                 | 0.68 | 0.79 | 0.25  | 0.25   | 0.25        |
| 270 (#2)                                  | 0.25                 | 0.37 | 0.70 | 0.24  | 0.25   | 0.24        |
| 366 (#2)                                  | 0.24                 | 0.27 | 0.65 | 0.24  | 0.24   | 0.23        |
| 340 (#2)                                  | 0.25                 | 0.18 | 0.39 | 0.24  | 0.25   | 0.24        |

### STANDARD DOUBLE GLAZED (ONE LOW-E ON SURFACE #2 OR #3 / STAINLESS STEEL SPACER)

|          |      |      |      |      |      |      |
|----------|------|------|------|------|------|------|
| 180 (#3) | 0.26 | 0.68 | 0.79 | 0.25 | 0.25 | 0.25 |
| 270 (#2) | 0.25 | 0.37 | 0.70 | 0.24 | 0.25 | 0.24 |
| 366 (#2) | 0.24 | 0.27 | 0.65 | 0.24 | 0.24 | 0.23 |
| 340 (#2) | 0.25 | 0.18 | 0.39 | 0.24 | 0.25 | 0.24 |

### STANDARD TRIPLE GLAZED (TWO LOW-E ON SURFACES #2 & #5 / STAINLESS STEEL SPACER)

|         |      |      |      |      |      |      |
|---------|------|------|------|------|------|------|
| 180/180 | 0.13 | 0.56 | 0.70 | 0.17 | 0.17 | 0.15 |
| 270/180 | 0.13 | 0.33 | 0.62 | 0.17 | 0.17 | 0.15 |
| 366/180 | 0.13 | 0.25 | 0.57 | 0.17 | 0.17 | 0.15 |
| 340/180 | 0.13 | 0.16 | 0.34 | 0.17 | 0.17 | 0.15 |

### OPTIONS W/ CAPILLARY TUBES – AIR FILL (TWO LOW-E ON SURFACES #2 & #5 / STAINLESS STEEL SPACER)

|         |      |      |      |      |      |      |
|---------|------|------|------|------|------|------|
| 366/180 | 0.16 | 0.25 | 0.57 | 0.18 | 0.18 | 0.17 |
|         |      |      |      |      |      |      |

### STANDARD TRIPLE GLAZED (TWO LOW-E ON SURFACES #2 & #5 / TRISEAL SUPER SPACER)

|         |      |      |      |      |      |      |
|---------|------|------|------|------|------|------|
| 180/180 | 0.13 | 0.56 | 0.70 | 0.16 | 0.17 | 0.15 |
| 270/180 | 0.13 | 0.33 | 0.62 | 0.16 | 0.16 | 0.15 |
| 366/180 | 0.13 | 0.25 | 0.57 | 0.16 | 0.16 | 0.15 |
| 340/180 | 0.13 | 0.16 | 0.34 | 0.16 | 0.16 | 0.15 |

### PREMIUM TRIPLE GLAZED (THREE LOW-E ON SURFACES #2, #4 & #6 / STAINLESS STEEL SPACER)

|             |      |      |      |      |      |      |
|-------------|------|------|------|------|------|------|
| 180/180/i89 | 0.12 | 0.53 | 0.68 | 0.16 | 0.16 | 0.14 |
| 270/180/i89 | 0.11 | 0.32 | 0.60 | 0.16 | 0.16 | 0.14 |
| 366/180/i89 | 0.11 | 0.24 | 0.56 | 0.16 | 0.16 | 0.14 |
| 340/180/i89 | 0.11 | 0.15 | 0.33 | 0.16 | 0.16 | 0.14 |

### PREMIUM TRIPLE GLAZED (THREE LOW-E ON SURFACES #2, #4 & #6 / TRISEAL SUPER SPACER)

|             |      |      |      |      |      |      |
|-------------|------|------|------|------|------|------|
| 180/180/i89 | 0.12 | 0.53 | 0.68 | 0.16 | 0.16 | 0.14 |
| 270/180/i89 | 0.11 | 0.32 | 0.60 | 0.15 | 0.15 | 0.14 |
| 366/180/i89 | 0.11 | 0.24 | 0.56 | 0.15 | 0.15 | 0.13 |

**Double-Glazed Glass:** 6mm-13mm-6mm

**Triple-Glazed Glass:** 6mm-13mm-6mm-13mm-6mm

**NOTE:** Exact thermal performance of casement, awning, and tilt and turn windows in final curtain wall assembly subject to specific project configuration. Performance of specific project configuration should be

# UNIVERSAL SERIES™

Curtain Wall Vent Adapter - Technical Data Sheet

**CASCADIA**  
WINDOWS & DOORS

## NAFS KEY PERFORMANCE DATA - WINDOWS & DOORS



| Type     | Tested Size [Inches] | Design Wind Pressure PSF (Pa) | Water Infiltration PSF (Pa) | NAFS Designators | Air Infiltration [L/s*M²] | Air Exfiltration [L/s*M²] |
|----------|----------------------|-------------------------------|-----------------------------|------------------|---------------------------|---------------------------|
| Outswing | CASEMENT             | 36" x 60"                     | 60 (2880)                   | 15 (730)         | AW-PG60-C                 | 0.01                      |
|          | CASEMENT             | 36" x 84"                     | 45 (2160)                   | 15 (730)         | CW-PG45-C                 | 0.06                      |
|          | AWNING               | 60" X 36"                     | 60 (2880)                   | 15 (730)         | AW-PG60-AP                | 0.05                      |
|          | AWNING               | 84" x 36"                     | 60 (2880)                   | 15 (730)         | CW-PG60-AP                | 0.00                      |
|          | AWNING               | 48" x 84"                     | 55 (2640)                   | 15 (730)         | CW-PG55-AP                | 0.01                      |
|          | AWNING               | 76" x 60"                     | 35 (1680)                   | 15 (730)         | CW-PG35-AP                | 0.00                      |
| Inswing  | TIlt & Turn          | 48" x 72"                     | 80 (3840)                   | 15 (730)         | CW-PG80-DAW               | 0.00                      |
|          | TIlt & Turn          | 60" x 99"                     | 45 (2160)                   | 15 (730)         | LC-PG45-AP                | 0.00                      |

**NOTE:** Dimensions above indicate NAFS performance tested sizes which may exceed common size limits available. For minimum/maximum sizes available, please consult Cascadia's Vent Size Charts.

Air Infiltration and Exfiltration tests the overall assembly at 75 Pa. All windows meet and surpass the US and Canadian air leakage performance requirements for A3/Fixed

## AVAILABLE WINDOW SIZES

|                         | OUTSIDE-OF-FRAME |                  |                 |                  | Performance Grade                           | Max. Weight (lbs) |
|-------------------------|------------------|------------------|-----------------|------------------|---|-------------------|
|                         | Min. Width (in)  | Min. Height (in) | Max. Width (in) | Max. Height (in) |   |                   |
| <b>OPERABLE WINDOWS</b> |                  |                  |                 |                  |   |                   |
| Casement (outswing)     | 18.75            | 22.625           | 36              | 72               | PG 60                                       | 220               |
| Awning (outswing)       | 20               | 22.625           | 55              | 47               | PG 55                                       | 176               |
| Tilt & Turn (inswing)   | 24               | 30               | 60              | 99               | PG 80 up to 48"x72" / PG 45 at larger sizes | 286               |